

York BLACK Edition: Sample List of Cartridge Load Settings

Switch to Right ☒ ON

Switch to Left ☐ OFF

Cartridge	Manufacturer Specified Load Setting	York Recommended LOAD SETTING Left and Right Channels
Nagaoka MP-110 MM	Cap: Not Specified Impedance: 47K Ω	100pF 47K Ω 
Denon DL-103 MC	Cap: Not Required Impedance: Not Specified	0pF 1K Ω 
Hana SL MC	Cap: Not Required Impedance: 400 Ω	0pF 470 Ω 
Nagaoka MP-300 MM	Cap: Not Specified Impedance: 47K Ω	150pF 47K Ω 
Ortofon 2M Black MM	Cap: 150-300pF Impedance: 47K Ω	250pF 47K Ω 
Audio Technica 150ANV MM	Cap: Not Specified Impedance: 47K Ω	150pF 47K Ω 
Goldring 1012GX MM	Cap: 150-200pF Impedance: 47K Ω	150pF 47K Ω 
Goldring 2100 MI	Cap: 100-200pF Impedance: 47K Ω	100pF 47K Ω 
Rega Exact2 MM	Cap: 100pF Impedance: 47K Ω	100pF 47K Ω 
Dynavector 20X2-H High Output MC	Cap: Not Required Impedance: 1K Ω	0pF 1K Ω 
Denon 103R MC	Cap: Not required Impedance: 100 Ω	0pF 100 Ω 



SIX ACOUSTIC